

TECHNICAL DATA

TAMPER

BT 30



Easy and ergonomic transport
Lightweight at around 30 kg




Compact dimensions
Narrow tamper foot for tight spaces



Used in cable construction
Specially designed for cable and pipeline construction

Shipping dimensions in m3
BT 30

0,175



Standard Equipment

- Engine Protection System
 -Protective engine covering
- Vibration insulated steering handle
- Single point lifting device
- Recoil starter
- Infinitely variable frequency
- 3-2-1 Warranty

Optional Equipment

- Service Kit

Dimensions in mm

	B	H	L	L1	W
BT 30	315	950	585	272	140

Technical Data

**BOMAG
 BT 30**

Weights

Operating weight	kg	32
Basic weight	kg	31

Dimensions

Working width (tamper plate)	mm	140
------------------------------------	----	-----

Drive

Engine manufacturer		Honda
Engine type		GX 50
Emission stage		EU Stage V / EPA III
Cooling		air
Number of cylinders		1
Performance SAE J 1349	kW	1,5
Fuel		Gasoline
Drive system		mech.
Fuel consump. aver. during operation	l/h	1,0

Exciter system

Frequency	Hz	10- 13,2
Jumping height	mm	45,0
Impact force	kN	10,0

Capacities

Fuel	l	0,6
------------	---	-----

Technical modifications reserved. Machines may be shown with options.



PRE 540 67 010

010825 Sa

BOMAG
 Hellerwald
 D-56154 Boppard
 P.O. Box 5162
 Tel. (0)6742 - 1000
 Fax (0)6742 - 3090

