

TECHNICAL DATA

TAMPER

BT 50



Maximum reliability and longevity
All around engine protection




Easy handling
Lightweight and ergonomic handle



Simple operation
Engine and fuel supply with combined switch

Shipping dimensions in m3

BT 50 0,262



Standard Equipment

- Engine Protection System
 - Protective engine covering
 - Paper air filter system with two stages
 - Automatic oil level control
 - Dual fuel filter system
- Vibration insulated steering handle
- Self-cleaning air filter
- Protective covering
- Single point lifting device
- Recoil starter
- Plastic castor as loading aid
- Infinitely variable frequency
- Combination of engine stop/fuel switch
- 3-2-1 Warranty

Optional Equipment

- h-/ rpm meter
- Transport device with puncture proof wheels
- Tamper foot widths (160-330mm)
- Tamper foot extensions
- Special painting
- Tool kit
- Service Kit
- TOUGH WARRANTY

Dimensions in mm

	B	H	L	L1	W
BT 50	350	1030	728	335	230

Technical Data

Weights

Operating weight CECE	kg	58
Basic weight	kg	57

Dimensions

Working width (tamper plate)	mm	230
------------------------------------	----	-----

Driving Characteristics

Working speed max.	m/min	20
Area coverage max.	m ² /h	276

Drive

Engine manufacturer	Honda
Engine type	GXR 120
Emission stage	CARB Phase 3
Cooling	air
Number of cylinders	1
Performance SAE J 1349	kW 2,8
Fuel	Gasoline
Drive system	mech.
Fuel comsump. aver. during operation	l/h 0,9

Exciter system

Frequency	Hz	10- 11,8
Impact force	kN	15,0
Jumping height	mm	70,0

Capacities

Fuel	l	3,0
------------	---	-----

Technical modifications reserved. Machines may be shown with options.

BOMAG

BT 50



PRE 541 60 010

121125 Sa01

BOMAG
 Hellerwald
 D-56154 Boppard
 P.O. Box 5162
 Tel. (0)6742 - 1000
 Fax (0)6742 - 3090

